

VEVOR

Affordable. Reliable. Home Improvement.

Telescopic Ladder

Model: MF-TLA380

VEVOR Support Center



MF-TLA380

VEVOR

Affordable. Reliable. Home Improvement.

Telescopic Ladder

MODEL:MF-TLA380



This is the original instruction, please read all manual instructions carefully before operating. VEVOR reserves a clear interpretation of our user manual. The appearance of the product shall be subject to the product you received. Please forgive us that we won't inform you again if there are any technology or software updates on our product.

SECURITY & WARNINGS

CAUTION: Please read AL Instructions before using!!

BEFORE USE

- 1.Ensure that you are fit enough to use the ladder.Certain medical conditions or medication,alcohol or drug abuse could make the use of the ladder unsafe.The weight capacity is 330 lbs.
- 2.When transporting ladders on the roof bars of a vehide or in a truck, ensure that it is suitably placed to prevent damage.
- 3.Inspect the ladder after delivery and before first use to confirm condition and operation of all parts.
- 4.Visually check that the ladder is not damaged and is safe to use whenever using
- 5.For professional users,regular periodic inspections are required.
- 6.Ensure that the ladder is suitable for the task.
- 7.D0 NOT USE A DAMAGED LADDER!
- 8.Remove any contamination from the ladder such as wet paint,mud,oil or snow.
- 9.Before using the ladder at work a risk assessment should be carried respecting the legislation in the country of use.

POSITIONING AND EXTENDING THE LADDER

- 1.D0 NOT EXCEED THE MAXIMUM LOAD (330 lbs).
- 2.D0 NOT overreach.Users should keep their buckle (naveljinside the stiles and both feet on the same step/rung during your working.
- 3.D0 NOT step off a leaning ladder at a higher level without additional security.
- 4.D0 NOT use standing ladders for access to another level.

5. DO NOT stand on the top three steps/rungs of a leaning ladder.
6. Ladders should ONLY be used for light work of short duration.
7. DO NOT use the ladders outside in adverse weather conditions, such as strong winds.
8. TAKE PRECAUTIONS AGAINST CHILDREN PLAYING ON AND AROUND THE LADDER.
9. Face to the ladder when ascending and descending.
10. Keep a secure grip on the ladder when ascending and descending.
11. DO NOT use the ladder as a bridge.
12. Wear suitable footwear when using the ladder.
13. Avoid excessive side loading (i.e. drilling brick and concrete).
14. DO NOT spend long periods on the ladder without regular breaks (fatigue is a safety risk).
15. Leaning ladders used for access to a higher level should be extended at least 1m above the landing point.
16. Equipment carried while using the ladder should be light and easy to handle.

OPENING THE LADDER

Note: The actual number of steps of the ladder shall prevail in kind.


Automatic locking: Each step/rung of your ladder has 2 locking pins.

The location of the locks are the two buttons on the bottom of each step/rung as displayed:

- Unlocked position (see Picture #1 below). Unlocked is RED !
- Locked positions (see Picture #2 below). The buttons are located under each step/rung. Locked is fully GREEN!



#1



#2

COMPLETE EXTENSION OF THE LADDER

Note: The actual number of steps of the ladder shall prevail in kind.

Place ladder on a firm and level ground, put one foot on the lowest step/rung.

Then pull top step/rung off up and check that the buttons are locked (Picture #2). Repeat the process with each of the next steps/rungs until the arms are completely extended. (see Picture #3 and #4)

CAUTION: Always check that all buttons are on the "LOCKED" position (Green), before you climb the ladder.



#3



#4

TROUBLESHOOTING INSTRUCTIONS

If there is a problem with your telescopic ladder during operation, please check the troubleshooting table below before calling the service department.

Troubleshooting Instructions		
Fault Phenomenon	Cause of Issue	Solution
Open the rear adder to lean left and right	The section of the adder does not expand properly	Take back the ladder and check whether each section is stuck, such as normal shrinkage. Re-open it and make sure that each section is in place (there are lock marks on both sides of the pedal)

PRODUCT TECHNICAL PARAMETERS

Product Name	TELESCOPIC LADDER
Model	MF-TLA380
Number of Floors	13 Layers
Maximum Bearing of Each Layer	150 kg

CLEANING INSTRUCTIONS

- Store the ladder in the closed position.
- Properly secure and support the ladder while in transit.
- Keep the ladder clean and free from all other harmful materials.

DISPOSAL

Dispose of all packaging, paper, cartons and plastic, plastic bags by your local recycling regulations. At the end of the product's lifespan please dispose of it at an authorized household waste recycling center.

Manufacturer: Shanghaimuxinmuyeyouxiangongsi

Address: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.

Imported to AUS: SIHAO PTY LTD. 1 ROKEVA STREET EASTWOOD NSW 2122 Australia

Imported to USA: Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

UK	REP	YH CONSULTING LIMITED. C/O YH Consulting Limited Office 147, Centurion House, London Road, Staines-upon-Thames, Surrey, TW18 4AX
-----------	------------	--

EC	REP	E-CrossStu GmbH Mainzer Landstr.69, 60329 Frankfurt am Main.
-----------	------------	--

